

Ditec Marine Products LLC
SAFETY DATA SHEET



Section 1: Identification

Product Name: Crystal Clear Product Code: Crystal

Ditec Marine Products, LLC
W229 N2512 Duplainville Road
Waukesha, WI 53186 USA
Tel: 1 800 572 4390

Emergency Phone:

CHEMTREC: Canada and USA - (800) 424-9300
CHEMTREC: In Mexico - 01-800-681-9531

Product Use: NA
Not recommended for: NA

Section 2: Hazard(s) Identification

GHS Ratings:

<p>Flammable liquid 2 Eye corrosive 2A Mutagen 1B</p>	<p>Flash point < 23°C and initial boiling point > 35°C (95°F) Eye irritant: Subcategory 2A, Reversible in 21 days Known to produce heritable mutations in human germ cells Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity</p>
<p>Carcinogen 1A Reproductive toxin 1A Organ toxin single exposure 3</p>	<p>Known Human Carcinogen Based on human evidence Based on human evidence Transient target organ effects- Narcotic effects- Respiratory tract irritation</p>
<p>Organ toxin repeated exposure 1</p>	<p>Significant toxicity in humans- Reliable, good quality human case studies or epidemiological studies Presumed significant toxicity in humans- Animal studies with significant and/or severe toxic effects relevant to humans at generally low exposure (guidanc</p>

GHS Hazards

H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P260	Do not breathe dust/fume/gas/mist/vapors/spray

P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash face, hands, and any exposed skin thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P314	Get Medical advice/attention if you feel unwell
P303+P361+P353	If on skin (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
P304+P340	If inhales: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	If exposed or concerned get medical advice / attention.
P337+P313	If eye irritation persists get medical advice / attention
P370+P378	In case of fire: Use ... for extinction
P405	Store locked up
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container in accordance with local/regional/national/international regulations

Danger



Section 3: Composition/Information on Ingredients

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Ethyl alcohol 64-17-5 40% - 50% Vapor Pressure: 42.979 mmHg	1000 ppm TWA; 1900 mg/m ³ TWA	1000 ppm STEL	NIOSH: 1000 ppm TWA; 1900 mg/m ³ TWA

Isopropyl alcohol 67-63-0 10% - 20% Vapor Pressure: 31.503 mmHg	400 ppm TWA; 980 mg/m3 TWA	400 ppm STEL 200 ppm TWA	NIOSH: 400 ppm TWA; 980 mg/m3 TWA 500 ppm STEL; 1225 mg/m3 STEL
--	-------------------------------	-----------------------------	--

Section 4: First-aid Measures

Inhalation

Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

Eye Contact

Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

Skin Contact

Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

Ingestion

If swallowed, do NOT induce vomiting. Give victim a glass of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Section 5: Fire-fighting Measures

Flash Point: 12 C (54 F)

LEL: 3.00

UEL:

Extinguishing Media

Use media suitable for the surrounding fire.

Specific Hazards Arising from the Chemical

None known.

Special Protective Equipment and Precautions for Firefighters

Special Information: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA / NIOSH approved or equivalent) and full protective gear.

Section 6: Accidental Release Measures

Spill and Leak Procedures

Section 7: Handling and Storage

Handling Procedures

Use with adequate ventilation. Avoid breathing dusts, mists, and vapors. Do not get in eyes, on skin, or on clothing. Wear eye protection and protective clothing. Wash thoroughly after handling.

Storage Requirements

Store containers in a cool, dry, well ventilated place. Keep container closed when not in use.

Section 8: Exposure Control/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Ethyl alcohol 64-17-5	1000 ppm TWA; 1900 mg/m3 TWA	1000 ppm STEL	NIOSH: 1000 ppm TWA; 1900 mg/m3 TWA

Isopropyl alcohol 67-63-0	400 ppm TWA; 980 mg/m3 TWA	400 ppm STEL 200 ppm TWA	NIOSH: 400 ppm TWA; 980 mg/m3 TWA 500 ppm STEL; 1225 mg/m3 STEL
------------------------------	-------------------------------	-----------------------------	--

ENGINEERING CONTROLS: Provide ventilation sufficient to maintain exposure below the recommended limits .

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant the use of a respirator.

SKIN PROTECTION: Wear impervious protective gloves . Wear protective gear as needed - apron, suit, boots .

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield .

OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

HYGIENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

Section 9: Physical and Chemical Properties

Boiling Range 78 to 100 °C	% Volume Volatile 0.00
Specific Gravity (SG) 0.888	Lbs VOC/Gallon Less Water 0.00

Section 10: Stability and Reactivity

Chemical Stability:

STABLE

Incompatible Materials

Conditions to Avoid

Hazardous Decomposition Products

Hazardous Polymerization

Hazardous polymerization will not occur.

Section 11: Toxicology Information

Mixture Toxicity

Inhalation Toxicity LC50: 205mg/L

Component Toxicity

67-63-0

Isopropyl alcohol

Oral LD50: 1,870 mg/kg (Rat) Dermal LD50: 4,059 mg/kg (Rabbit)

Routes of Entry:

Inhalation

Ingestion

Skin contact

Eye contact

Target Organs

Effects of Overexposure

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
-------------------	--------------------	-----------------	--------------------------

Section 12: Ecological Information

Component Ecotoxicity

Ethyl alcohol	96 Hr LC50 Oncorhynchus mykiss: 12.0 - 16.0 mL/L [static]; 96 Hr LC50 Pimephales promelas: >100 mg/L [static]; 96 Hr LC50 Pimephales promelas: 13400 - 15100 mg/L [flow-through] 48 Hr LC50 Daphnia magna: 9268 - 14221 mg/L; 48 Hr EC50 Daphnia magna: 2 mg/L [Static]		
Isopropyl alcohol	96 Hr LC50 Pimephales promelas: 9640 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 11130 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >1400000 µg/L 48 Hr EC50 Daphnia magna: 13299 mg/L 96 Hr EC50 Desmodemus subspicatus: >1000 mg/L; 72 Hr EC50 Desmodemus subspicatus: >1000 mg/L		

Section 13: Disposal Considerations

Dispose of in accordance with local, state and federal regulations.

Section 14: Transportation Information

This product is non-regulated for land transport.

Section 15: Regulatory Information

SARA 313

This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know-Act of 1986 (40 CFR 372):

67-63-0 Isopropyl alcohol 10 - 20%

This information must be included in all SDSs that are copied and distributed for this material.

TSCA 8(b) Inventory

67-63-0 Isopropyl alcohol
64-17-5 Ethyl alcohol

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
----------------	-------------------	------------------------------

Section 16: Other Information

Date Prepared: 12/17/2020

Reviewer Revision

Disclaimer

The information herein is believed to be correct, but does not claim to be all inclusive and should be used only as a guide. Neither the above named supplier nor any of its affiliates or subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All chemical reagents must be handled with the recognition that their chemical, physiological, toxicological, and hazardous properties have not been fully investigated or determined. All chemical reagents should be handled only by individuals who are familiar with their potential hazards and who have been fully trained in proper safety, laboratory, and chemical handling procedures. Although certain hazards are described herein, we can not guarantee that these are the only hazards which exist. Our SDS are based only on data available at the time of shipping and are subject to change without notice as new information is obtained. Avoid long storage periods since the product is subject to degradation with age and may become more dangerous or hazardous. It is the responsibility of the user to request updated SDS for products that are stored for extended periods. Disposal of unused product must be undertaken by qualified personnel who are knowledgeable in all applicable regulations and follow all pertinent safety precautions including the use of appropriate protective equipment (e.g. protective goggles, protective clothing, breathing equipment, face mask, fume hood). For proper handling and disposal, always comply with federal, state and local regulations.