

Conforms to Regulation (EC) No. 1907/2006 (REACH)

# Safety Data Sheet

## Section 1. Chemical Product and Company Identification

PRODUCT NAME: GLASSTEC

SYNONYMS:  
PRODUCT CODES:

MANUFACTURER: Ditec Marine Products,  
DIVISION: Industrial coatings  
ADDRESS: W229 N2519 Duplainville Rd., Waukesha, WI 53186

EMERGENCY PHONE: + 800-572-4390  
CHEMTREC PHONE: 1 (800) 424-9300  
OTHER CALLS: Chemtrec: 1-800-424-9300 (24H)

CHEMICAL NAME: Ethyl Alcohol Solution  
CHEMICAL FAMILY: Composition from modified hybrid materials in denatured ethanol solution  
CHEMICAL FORMULA:

PRODUCT USE: Hydrophobic Glass Coating, Easy to Clean coating  
PREPARED BY: Ditec Marine Products, LLC

SECTION 1 NOTES:

## Section 2. Hazard Identification

### 2.1 Classification of substance or mixture

Regulation (EC) No 1272/2008 (CLP)	
Hazard classes / Hazard categories	Hazard Statement
Flammable liquids, Category 2	H225

67/548/EEC or 1999/45/EC	
Hazard Characteristics	R-phrases(s)
Highly flammable.	R11

### 2.2 Label elements

Hazard pictograms



Signal word (GHS)

: **Danger**

Hazard statements (GHS)

Eye Irritation: Category 2A  
Flammable Liquids: Category 2

Precautionary statements (GHS)

H225 - Highly flammable liquid and vapour  
H302 - Harmful if swallowed  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation

**Safety Hazards**  
**Environmental Hazards**

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools  
Highly flammable. Flammable liquid and vapour.  
:Not classified as dangerous for the environment.

See Toxicological Information (section 11)

### Section 3. Composition, Information on Ingredients

Name	CAS	%	Classification
Ethanol Alcohol, denatured	64-17-5	> 85 %	65, 66,11
Isopropanol Alcohol	67-63-0	> 5 %	65, 66,11
Non-hazardous		Balance to 100 %	--

### Section 4. First Aid Measures

<b>Inhalation</b>	:	Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
<b>Skin Contact (S24)</b>	:	Irritating to skin. Remove affected person from source of contamination. Wash contaminated skin promptly with soap or mild detergent and water. Remove clothing promptly, if soaked through, and wash as above.
<b>Eye Contact</b>	:	Irritating to eyes. Can be damaging if large amount is splashed into eyes. Wash eyes promptly with plenty of water, while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.
<b>Ingestion</b>	:	If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
<b>Inhalation</b>	:	Occupational exposure limits (8-hour reference period) 1000 ppm (1900 mg/m <sup>3</sup> ) Intoxicating if continuously inhaled for a long period of time. Move the person to fresh air, immediately perform artificial respiration if breathing has stopped. When breathing is difficult, properly-trained personnel may administer oxygen. Keep the person warm and at rest. Get medical attention promptly.

### Section 5. Fire Fighting Measures

<b>Extinguishing Media</b>	Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable Extinguishing Media</b>	Do not use water in a jet.
<b>Special hazards arising from substance or mixture</b>	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Ethanol burns with a smokeless blue flame that is not always visible in normal light.
<b>Advice for fire-fighters</b>	Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.
<b>Additional Advice</b>	If possible remove containers from the danger zone. If the fire cannot be extinguished the only course of action is to evacuate immediately. Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.

### Section 6. Accidental Release Measures

<b>Large Spill and Leak</b>	<p>Small quantities can be mopped or wiped up with rags. Eliminate all ignition sources. Keep unnecessary personnel away. Stop leak if without risk. Use suitable protective equipment (Section 8). For small spills add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion proof means to transfer material to a sealed, appropriate container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Minimize contact of spilled material with soils to prevent runoff to surface waterways</p> <p>Vapor can travel for considerable distances both above and below the ground surface. Underground services (drains, pipelines, cable ducts) can provide preferential flow paths. Do not breathe fumes, vapor.</p>
-----------------------------	---

## Section 7. Handling and Storage

<b>Handling</b>	Keep container closed. Use only with adequate ventilation. Keep away from heat, sparks and flame. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Use explosion-proof electrical (ventilating, lighting and material handling equipment).
<b>Storage</b>	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Keep container tightly closed.
<b>General Precautions</b>	Avoid breathing vapors or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Air-dry contaminated clothing in a well-ventilated area before laundering.

## Section 8. Exposure Controls, Personal Protection

### 8.1 Control Parameters

#### Occupational Exposure Limits

Material	Source	Type	ppm	mg/m3	Notation
Ethanol	EH40 WEL	TWA	1,000 ppm	1,920 mg/m3	

Material	Source	Type	ppm	mg/m3	OSHA PE
Isopropanol Alcohol	EH40 WEL	TWA	400 ppm	1,920 mg/m3	400 ppm

### 8.2 Exposure Controls

#### General Information

: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

#### VENTILATION

Store in a well-ventilated area. Work area must be well ventilated. Use engineering controls to reduce air contamination to permissible exposure level

#### RESPIRATORS

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Occupational Exposure Level (OEL).

#### PROTECTIVE GLOVES

Wear gloves of impervious material e.g. laminated film or nitrile.  
Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken.

#### EYE PROTECTION:

Wear approved chemical safety goggles where eye exposure is reasonably probable. Contact lenses should not be worn when working with this chemical!

#### OTHER PROTECTION

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station and safety shower. If engineering controls are not effective in controlling airborne exposure, then an approved respirator with a replaceable organic vapor filter should be used.

Wear appropriate clothing to prevent repeated or prolonged skin contact.

## Section 9. Physical and Chemical Properties

Appearance	Clear colorless	Odor Odor threshold	Alcoholic 49 ppm
PHYSICAL STATE:	Liquid	pH AS SUPPLIED:	Ca 2
BOILING POINT F: C:	208 78	MELTING POINT F: C:	
VAPOR PRESSURE (mmHg):	5.9 kPa [20°C]	VAPOR DENSITY (AIR = 1):	1.6
VOLATILE ORGANIC COMPOUNDS (VOC):		MOLECULAR WEIGHT: VISCOSITY:	
SPECIFIC GRAVITY (H2O = 1):	0.78 0.7 g / ml	<b>Flashpoint</b>	<b>F: 61</b> <b>C: 16</b>
EVAPORATION RATE: BASIS (=1):	1.7		yes

## Section 10. Stability and Reactivity

**Stability and Reactivity** Stable under recommended storage conditions.

**Conditions to avoid** Heat, flames and sparks. Extremes of temperature and direct sunlight

**Incompatibility** Alkali metals, Ammonia, Oxidizing agents, Peroxides

## Section 11. Toxicological Information

**LD/LC50 values that are relevant:**

LD50: ORL-RAT, 7,060 mg/kg (Ethanol)

**Carcinogenicity Classification:**

IARC (International Agency for Research on Cancer) - Not Listed

NTP (National Toxicology Program) - Not Listed

**Eye:** Produces irritation, characterized by a burning sensation, redness, tearing, inflammation,

**Ingestion:** May cause gastrointestinal irritation with nausea, vomiting, and diarrhea. May cause systemic toxicity with acidosis. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea.

**Inhalation:** Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. Causes respiratory tract irritation. Vapors may cause dizziness or suffocation.

**Skin:** Causes moderate skin irritation. Dry skin

**Chronic:** Prolonged or repeated skin contact may cause dermatitis. Chronic inhalation and ingestion may cause effects similar to those of acute inhalation and ingestion. Prolonged ingestion may cause liver, kidney, and heart damage.

## Section 12. Ecological Information

**Eco-toxicity:** Not available.

**BOD5 and COD:** Not available.

### Products of Biodegradation:

Possibly hazardous short-term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.

The product is biodegradable and has not been shown to interfere in anyway with waste water treatment plants. In high concentrations it harms fish and plankton.

### Special Remarks on the

**Products of Biodegradation:** Not available.

## Section 13. Disposal Considerations

**Waste Information** Waste must be disposed of in accordance with federal, state and local environmental control regulations.

### Material Disposal

Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

### Container Disposal

Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion.

## Section 14 Transport Information

### Land transport (ADR/RID): ADR

14.1 UN No.	1170
14.2 UN Proper Shipping Name	ETHYL ALCOHOL SOLUTION
14.3 Transport Hazard Class	3
14.4 Packing group	II
Danger label (primary risk)	3
14.5 Environmental Hazard	No
14.6 Special Precautions for user	Special Precautions: Refer to Chapter 7, Handling & Storage, for specialprecautions which a user needs to be aware of or needs to comply with in connection with transport

### DOT

DOT Shipping Name:	ETHYL ALCOHOL SOLUTION
Canada TDG:	ETHYL ALCOHOL SOLUTION
DOT Hazard Class:	3,
Packing group	II.
Identification Number:	UN1170. UN Number: UN1170.

### RID

14.1 UN No.	1170
14.2 UN Proper Shipping Name	: ETHYL ALCOHOL SOLUTION
14.3 Transport Hazard	3
14.4 Packing group	II
Danger label (primary risk)	3
14.5 Environmental Hazard	No
14.6 Special Precautions for user	Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport

**Sea transport (IMDG Code):**

14.1 UN No.	UN 1170
14.2 UN Proper Shipping Name	ETHYL ALCOHOLSOLUTION
14.3 Transport Hazard Class	3
14.4 Packing group	II EMS No.: F-E, S-D
14.5 Marine pollutant	No
14.6 Special Provision	Special Provision: 144

**Air transport (IATA):**

14.1 UN No.	1170
14.2 UN Proper Shipping Name	ETHYL ALCOHOL SOLUTION
14.3 Transport Hazard Class	3
14.4 Packing group	II

Packaging Instructions (passenger &amp; cargo): 353

Packaging Instructions (cargo only): 364

Special Provision: A 46

**Section 15. Regulatory Information****U.S. Regulations****Other Regulations**

US INVENTORY (TSCA): All components are listed or exempted.

Australia inventory (AICS): All components are listed or exempted.

Canada inventory: All components are listed or exempted.

Japan inventory: All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Korea inventory: All components are listed or exempted.

New Zealand Inventory (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

United States inventory (TSCA 8b): All components are listed or exempted.

Taiwan inventory (CSNN): All components are listed or exempted.

**Labeling according to Regulation GHS**

H225: Highly flammable liquid and vapor.

**ENVIRONMENTAL HAZARDS:**

Not classified as an environmental hazard under GHS criteria.

**CLP Precautionary statements****Prevention**

P102: Keep out of reach of children.

P210: Keep away from heat/sparks/open flames/hot surfaces.

– No smoking.

P233: Keep container tightly closed.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Storage****Labeling according to Directive 1999/45/EC**

P403+P235: Store in a well-ventilated place. Keep cool.

EC Symbols

F Highly flammable.

EC Classification

Highly flammable.

EC Risk Phrases

R11 Highly flammable.

EC Safety Phrases

S2 Keep out of the reach of children.

S7 Keep container tightly closed.

S16 Keep away from sources of ignition - No smoking

**Section 16. Other Information**

**To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.**