

DITEC MARINE PRODUCTS, LLC
SAFETY DATA SHEET



Section 1: Identification

Product Name: MVP

Product Code: H007039

Ditec Marine Products, LLC
W229 N2512 Duplainville Road
Waukesha, WI 53186 USA
Tel: 1 800 572 4390

Emergency Phone:

CHEMTREC: Canada and USA - (800) 424-9300
CHEMTREC: In Mexico - 01-800-681-9531

Product Use: Industrial

Not recommended for: NA

Section 2: Hazard(s) Identification

GHS Ratings:

Flammable liquid	3	Flash point $\geq 23^{\circ}\text{C}$ and $\leq 60^{\circ}\text{C}$ (140°F)
Skin corrosion/irritation	2	Reversible adverse effects in dermal tissue, Draize score: $\geq 2.3 < 4.0$ or persistent inflammation
Germ cell mutagenicity	1B	Known to produce heritable mutations in human germ cells Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogenicity	1B	Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity
Specific target organ toxicity single exposure	3	Transient target organ effects- Narcotic effects- Respiratory tract irritation
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity ≥ 20.5 mm ² /s at 40° C.

GHS Hazards

H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash face, hands, and any exposed skin thoroughly after handling

P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P321	Specific treatment (see first aid treatment on SDS)
P331	Do NOT induce vomiting
P362	Take off contaminated clothing and wash before reuse
P301+P310	If swallowed: Immediately call a POISON CENTER or doctor / physician.
P302+P352	If on skin: Wash with plenty of soap and water.
P303+P361+P353	If on skin (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
P304+P340	If inhales: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308+P313	If exposed or concerned get medical advice / attention.
P332+P313	If skin irritation occurs: Get medical advice / attention
P370+P378	In case of fire: Use ... for extinction
P405	Store locked up
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container in accordance with local/regional/national/international regulations

Danger



Section 3: Composition/Information on Ingredients

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Naphtha, petroleum, hydrotreated heavy 64742-48-9 90% - 100%			
Trade Secret 1% - 5%			

Section 4: First-aid Measures

Inhalation

Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

Eye Contact

Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

Skin Contact

Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

Ingestion

If swallowed, do NOT induce vomiting. Give victim a glass of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Section 5: Fire-fighting Measures

Extinguishing Media

Use media suitable for the surrounding fire. Carbon Dioxide, Dry Chemical, Foam, Water Fog

Specific Hazards Arising from the Chemical

Flammable liquid and vapor. Vapors/dust may cause flash fire or explosion. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning.

Special Protective Equipment and Precautions for Firefighters

Special Information: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA / NIOSH approved or equivalent) and full protective gear. Avoid use of solid water streams. Water spray to cool containers or protect personnel. Use with caution. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

Section 6: Accidental Release Measures

Spill and Leak Procedures

Wear appropriate personal protective equipment. (See Exposure Controls / Personal Protection Section.)Wear a self-contained breathing apparatus and appropriate personal protective equipment. (See Exposure Controls/Personal Protection Section)Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. May cause slipping hazard. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. A vapor suppressing foam may be used to reduce vapors. Collect spilled materials for disposal. Use only non-combustible material for clean-up. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Recover by pumping (use an explosion proof or hand pump).

Section 7: Handling and Storage

Handling Procedures

Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Take precautionary measures against static discharge. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Follow all SDS/label precautions even after containers are emptiedbecause they may retain product residues.

Storage Requirements

Store containers in a cool, dry, well ventilated place. Keep container closed when not in use.

Section 8: Exposure Control/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
-------------------------	----------------------	-----------------------	-----------------------

Naphtha, petroleum, hydrotreated heavy 64742-48-9			
Trade Secret N/A			

ENGINEERING CONTROLS: Provide ventilation sufficient to maintain exposure below the recommended limits .

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant the use of a respirator.

SKIN PROTECTION: Wear impervious protective gloves . Wear protective gear as needed - apron, suit, boots.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

HYGENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

Section 9: Physical and Chemical Properties
--

<p>Appearance: Clear White to Slightly Yellow Liquid</p> <p>Vapor Pressure: Not Available</p> <p>Vapor Density: Not Available</p> <p>Density: 0.762</p> <p>Freezing point: Not Available</p> <p>Boiling range: Not Available</p> <p>Evaporation rate: Not Available</p> <p>Explosive Limits: Not Available</p> <p>Autoignition temperature: Not Available</p> <p>Viscosity: Not Available</p>	<p>Odor: Not Available</p> <p>Odor threshold: Not Available</p> <p>pH: Not Available</p> <p>Melting point: Not Available</p> <p>Solubility: Not Available</p> <p>Flash point: Not Available</p> <p>Flammability: Not Available</p> <p>Specific Gravity: Not Available</p> <p>Decomposition temperature: Not Available</p> <p>Grams VOC less water: Not Available</p>
---	--

Section 10: Stability and Reactivity

Chemical Stability:

STABLE

Incompatible Materials

Avoid contact with moisture and/or water . Prevent contact with strong oxidizing agents.

Conditions to Avoid

Avoid impact,friction, heat, sparks, flame and sources of ignition

Hazardous Decomposition Products

Toxic gases/fumes are given off during burning or thermal decomposition . May release hydrogen fluoride under fire conditions. During combustion ,carbon monoxide may be formed. During combustion, carbon dioxide may be formed.

Hazardous Polymerization

Hazardous polymerization will not occur.

Section 11: Toxicology Information

Mixture Toxicity

Dermal Toxicity LD50: 3,383mg/kg

Component Toxicity

64742-48-9 Naphtha, petroleum, hydrotreated heavy
Oral LD50: 5,000 mg/kg (Rat) Dermal LD50: 3,160 mg/kg (Rabbit)

Routes of Entry:

Inhalation
Ingestion
Skin contact
Eye contact

Target Organs

Effects of Overexposure

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
64742-48-9	Naphtha, petroleum, hydrotreated heavy	90% - 100%	Naphtha, petroleum, hydrotreated heavy: EU REACH: Present (P)

Section 12: Ecological Information

Component Ecotoxicity

Naphtha, petroleum, hydrotreated heavy 96 Hr LC50 Pimephales promelas: 2200 mg/L

Section 13: Disposal Considerations

Dispose of in accordance with local, state and federal regulations.

Section 14: Transportation Information

The following is for US DOT Highway Transportation. Other modes/jurisdictions may have different classifications.

UN Code: 1993 **DOT Name:** Combustible liquid, n.o.s. (petroleum distillates)

Hazard Class: 3 **Packing Group:** III

Section 15: Regulatory Information

CERCLA/SARA Hazardous Substances

OSHA Process Safety Management Highly Hazardous Chemicals

U.S. Clean Air Act Toxic and Flammable Substances

SARA 313

This product contains the following EPCRA section 313 chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know-Act of 1986 (40 CFR 372):

This information must be included in all SDSs that are copied and distributed for this material.

TSCA 8(b) Inventory

64742-48-9 Naphtha, petroleum, hydrotreated heavy

Country

Regulation

All Components Listed

Section 16: Other Information

Date Prepared: 7/12/2022

Disclaimer

The information herein is believed to be correct, but does not claim to be all inclusive and should be used only as a guide. Neither the above named supplier nor any of its affiliates or subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All chemical reagents must be handled with the recognition that their chemical, physiological, toxicological, and hazardous properties have not been fully investigated or determined. All chemical reagents should be handled only by individuals who are familiar with their potential hazards and who have been fully trained in proper safety, laboratory, and chemical handling procedures. Although certain hazards are described herein, we can not guarantee that these are the only hazards which exist. Our SDS are based only on data available at the time of shipping and are subject to change without notice as new information is obtained. Avoid long storage periods since the product is subject to degradation with age and may become more dangerous or hazardous. It is the responsibility of the user to request updated SDS for products that are stored for extended periods. Disposal of unused product must be undertaken by qualified personnel who are knowledgeable in all applicable regulations and follow all pertinent safety precautions including the use of appropriate protective equipment (e.g. protective goggles, protective clothing, breathing equipment, face mask, fume hood). For proper handling and disposal, always comply with federal, state and local regulations.